

HIKVISION[®]

HiWatch Series



QUARTERLY FEATURED PRODUCTS | 2017 Q3

CONTENTS

PAGE 02

IP CAMERAS

PAGE 03

TVI CAMERAS

PAGE 04

NVR

PAGE 05

DVR

PAGE 06

KITS

PAGE 07

ASSOCIATED PRODUCTS

2MP FIXED FOCAL LENS NETWORK CAMERA

IPC-B120

2MP Network Bullet Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 2.8 / 4 / 6 mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- IP67
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-B220

2MP Network Bullet Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 4/6mm fixed focal lens
- 4mm:83°, 6mm:55°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-B220-D

2MP Network Bullet Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 4/6mm fixed focal lens
- 4mm:83°, 6mm:55°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- Mobile Monitoring

IPC-T120

2MP Network Turret Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 2.8/4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- True Day and Night
- 10m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-T120-D

2MP Network Turret Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 2.8/4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- True Day and Night
- 10m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- Mobile Monitoring

IPC-D120

2MP Network Dome Camera



Variants:
2.8mm,
4mm,
6mm

- 1/2.8" progressive scan CMOS
- 2.8/4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- IP67 + IK10 Vandal proof
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

2MP VARI-FOCAL LENS NETWORK CAMERA

IPC-B620-V

2MP Network Bullet Camera



- 1/2.8" progressive scan CMOS
- 2.8 - 12mm manual vari-focal lens
- View angle 100°-35°
- IP67 Vandal proof
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-B620-Z

2MP Network Bullet Camera



- 1/2.8" progressive scan CMOS
- 2.8 - 12mm motorized vari-focal lens
- View angle 100°-35°
- IP67 Vandal proof
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

4MP FIXED FOCAL LENS NETWORK CAMERA

IPC-T620-Z

2MP Network Turret Camera



- 1/2.8" progressive scan CMOS
- 2.8 - 12mm motorized vari-focal lens
- View angle 100°-35°
- IP67 Vandal proof
- True Day and Night
- Up to 30m IR range
- Dual stream
- 120dB true WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-B140

4MP Network Bullet Camera



Variants:
2.8mm,
4mm,
6mm

- 1/3" progressive scan CMOS
- 2.8 / 4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital Wide Dynamic Range
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-D140

4MP Network Dome Camera



Variants:
2.8mm,
4mm,
6mm

- 1/3" progressive scan CMOS
- 2.8 / 4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- IP67 + IK10 Vandal proof
- True Day and Night
- Up to 30m IR range
- Dual stream
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-T140

4MP Network Turret Camera



Variants:
2.8mm,
4mm,
6mm

- 1/3" progressive scan CMOS
- 2.8 / 4/6mm fixed focal lens
- 2.8mm : 105.8°; 4mm : 83.6°; 6mm : 55°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

4MP VARI-FOCAL LENS NETWORK CAMERA

IPC-B640-V

4MP Network Bullet Camera



- 1/3" progressive scan CMOS
- 2.8 - 12mm manual vari-focal lens
- View angle 108°-31°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-B640-Z

4MP Network Bullet Camera



- 1/3" progressive scan CMOS
- 2.8 - 12mm motorized vari-focal lens
- View angle 108°-31°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

IPC-T640-Z

4MP Network Turret Camera



- 1/3" progressive scan CMOS
- 2.8 - 12mm motorized vari-focal lens
- View angle 108°-31°
- IP67
- True Day and Night
- Up to 30m IR range
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- Mobile Monitoring

TVI CAMERAS

2MP FIXED FOCAL LENS TURBO HD CAMERA

THC-B120

2MP EXIR Bullet Camera



Variants:
2.8mm,
3.6mm,
6mm

- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 20 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

THC-D220

2MP Vandal Proof IR Dome Camera



Variants:
2.8mm,
3.6mm,
6mm

- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 105.8° ; 3.6mm : 84.3° ; 6mm : 55.4°
- True day and night
- Up to 20 m IR distance
- IP66 + IK10 vandal proof
- OSD menu
- Up the Coax (HIKVISION-C)

THC-T120

2M EXIR Turret Camera



Variants:
2.8mm,
3.6mm,
6mm

- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 20 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

THC-B220

2MP EXIR Bullet Camera



Variants:
2.8mm,
3.6mm,
6mm

- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

2MP PTZ TURBO HD CAMERA

THC-T220

2M EXIR Turret Camera



Variants:
2.8mm,
3.6mm,
6mm

- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

PTZ-T7230I-A

2M Turbo HD IR Speed dome



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 30x optical zoom, focal length 4-120mm
- 16x digital zoom
- 120m IR distance
- 3D DNR, Digital WDR, BLC
- TVI and CVBS dual output
- True day and night
- IP66

2MP VARI-FOCAL LENS TURBO HD CAMERA

THC-B220-V

2MP IR Bullet Camera



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8-12mm manual vari-focal lens
- View angle: 102.25° ~32°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

THC-B220-Z

2MP IR Bullet Camera



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8-12mm motorized vari-focal lens
- View angle: 102.25° ~32°
- True day and night
- 120dB true WDR
- DNR, Smart IR
- Up to 40 m IR distance
- IP67

THC-T220-V

2 MP IR Turret Camera



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8-12mm manual vari-focal lens
- View angle: 102.25° ~32°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

THC-T220-Z

2 MP EXIR Turret Camera



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8-12mm motorized vari-focal lens
- View angle: 102.25° ~32°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP67

THC-D220-Z

2 MP EXIR Dome Camera



- 2 megapixel high-performance CMOS
- Analog HD output, up to 1080p resolution
- 2.8-12mm motorized vari-focal lens
- View angle: 102.25° ~32°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP67+IK8

3MP FIXED FOCAL LENS TURBO HD CAMERA

THC-B230

3MP EXIR Turret Camera



Variants:
2.8mm,
3.6mm,
6mm

- 3 megapixel high-performance CMOS
- Analog HD output, up to 2052 × 1536 resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- IP66

THC-T230

3MP EXIR Bullet Camera



Variants:
2.8mm,
3.6mm,
6mm

- 3 megapixel high-performance CMOS
- Analog HD output, up to 2052 × 1536 resolution
- 2.8/3.6/6mm fixed focal lens
- 2.8mm : 92° ; 3.6mm : 70.9° ; 6mm : 56.7°
- True day and night
- DNR, Smart IR
- Up to 40 m IR distance
- IP66

NVR 100 SERIES

NVR-104-A



- Up to 4 channels network cameras
- H.264/H.264+ compression
- Recording at up to 4 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 40Mbps Out: 40Mbps
- Support up to 6TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management

NVR-104-A/4P



- Up to 4 channels network cameras
- H.264/H.264+ compression
- Recording at up to 4 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 40Mbps Out: 40Mbps
- Support up to 6TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Built-in 4 Ports 100Mbps PoE Switch

NVR-108-A



- Up to 8 channels network cameras
- H.264/H.264+ compression
- Recording at up to 4 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 60Mbps Out: 40Mbps
- Support up to 6TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management

NVR-108-A/8P



- Up to 8 channels network cameras
- Recording at up to 4 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 60Mbps Out: 40Mbps
- Support up to 6TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Built-in 8 Ports 100Mbps PoE Switch

NVR-104M-A



- Up to 4 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 40Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management

NVR-104M-A/4P



- Up to 4 network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 40Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Built-in 4 Ports 100Mbps PoE Switch

NVR 200M SERIES

NVR-108M-A



- Up to 8 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- Bandwidth; In: 80Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management

NVR-208M-A/8P



- Up to 8 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 2 SATA interfaces
- Bandwidth; In: 80Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Gigabit Ethernet Network Interface
- Built-in 8 Ports 100Mbps PoE Switch

NVR-216M-A



- Up to 16 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 2 SATA interfaces
- Bandwidth; In: 160Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Gigabit Ethernet Network Interface

NVR-216M-A/8P



- Up to 16 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 2 SATA interfaces
- Bandwidth; In: 160Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Gigabit Ethernet Network Interface
- Built-in 8 Ports 100Mbps PoE Switch

NVR-216M-A/16P



- Up to 16 channels network cameras
- Recording at up to 6 MP resolution
- HDMI/VGA output at 1080p resolution
- 2 SATA interfaces
- Bandwidth; In: 160Mbps Out: 80Mbps
- Support up to 4TB HDD
- Support Multiple VCA
- Smart search & Playback
- Hik-connect for easy network management
- Gigabit Ethernet Network Interface
- Built-in 16 Ports 100Mbps PoE Switch

DVR

DVR 100G SERIES

DVR-104G-F1



- 4 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 4ch Synchronous playback
- Hik-connect for easy network management

DVR-108G-F1



- 8 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 12fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 8ch Synchronous playback
- Hik-connect for easy network management

DVR-116G-F1



- 16 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 12fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 16ch Synchronous playback
- Hik-connect for easy network management

DVR 200Q SERIES

DVR-204Q-F1



- 4 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 3M@12fps, 1080p@25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 4ch Synchronous playback
- Hik-connect for easy network management

DVR-208Q-F1



- 8 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 3M@12fps, 1080p@25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 8ch Synchronous playback
- Hik-connect for easy network management

DVR-216Q-F1



- 16 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- HDMI/VGA output at 4K/2K resolution
- 1 SATA interface
- 3M@12fps, 1080p@25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Smart search
- 16ch Synchronous playback
- Hik-connect for easy network management
- Gigabit Ethernet Interface

DVR 200G SERIES

DVR-204G-F1



- 4 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- Up to 1-ch 960p IP cameras input
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Supports Multiple VCA (events detection)
- Smart Search & Playback
- Hik-connect for easy network management

DVR-208G-F1



- 8 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- Up to 2-ch 1080p IP cameras input
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Supports Multiple VCA (events detection)
- Smart Search & Playback
- Hik-connect for easy network management

DVR-216G-F1



- 16 HD TVI/HDCVI/AHD/CVBS signal input
- H.264/H.264+ compression
- Up to 2-ch 1080p IP cameras input
- HDMI/VGA output at 1080p resolution
- 1 SATA interface
- 1080p Lite @ 25fps/ch
- Support up to 6TB HDD
- VQD (Video Quality Diagnostics)
- Supports Multiple VCA (events detection)
- Smart Search & Playback
- Hik-connect for easy network management

DVR KITS

T104Q-A/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: n/a
- Camera: 2M
- Camera Q'ty: 4
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 92°

T104Q-B/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: n/a
- Camera: 2M
- Camera Q'ty: 4
- Type: Turret
- IR: Yes
- Lens: 2.8mm
- FOV: 92°

T108Q-A/2T



- Max Channels: 8
- SATA Interface: 1
- Included HDD: 2T
- Built-in PoE: n/a
- Camera: 2M
- Camera Q'ty: 6
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 92°

NVR KITS

T108Q-B/2T



- Max Channels: 8
- SATA Interface: 1
- Included HDD: 2T
- Built-in PoE: n/a
- Camera: 2M
- Camera Q'ty: 6
- Type: Turret
- IR: Yes
- Lens: 2.8mm
- FOV: 92°

I104-A/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: 4 Port
- Camera: 2M
- Camera Q'ty: 4
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I104-B/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: 4 Port
- Camera: 2M
- Camera Q'ty: 4
- Type: Dome
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I108-A/2T



- Max Channels: 8
- SATA Interface: 1
- Included HDD: 2T
- Built-in PoE: 8 Port
- Camera: 2M
- Camera Q'ty: 6
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I108-B/2T



- Max Channels: 8
- SATA Interface: 1
- Included HDD: 2T
- Built-in PoE: 8 Port
- Camera: 2M
- Camera Q'ty: 6
- Type: Dome
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I104M-A/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: 4 Port
- Camera: 4M
- Camera Q'ty: 4
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I104M-B/1T



- Max Channels: 4
- SATA Interface: 1
- Included HDD: 1T
- Built-in PoE: 4 Port
- Camera: 4M
- Camera Q'ty: 4
- Type: Turret
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I208M-A/2T



- Max Channels: 8
- SATA Interface: 2
- Included HDD: 2T
- Built-in PoE: 8 Port
- Camera: 4M
- Camera Q'ty: 6
- Type: Mini Bullet
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

I208M-B/2T



- Max Channels: 8
- SATA Interface: 2
- Included HDD: 2T
- Built-in PoE: 8 Port
- Camera: 4M
- Camera Q'ty: 6
- Type: Turret
- IR: Yes
- Lens: 2.8mm
- FOV: 105.8°

ASSOCIATED PRODUCTS

DOORBELL

DB-120A-IW



- 1080P with ultra-wide angle (180°)
- two-way audio with the mobile App
- Self-adaptive IR supplement
- 5-meter IR distance
- Supports the storage and playback via TF card
- Supports connecting to the mechanical chime
- 802.11G Wi-Fi

DB-210P-I



- 720P
- 80° wide angle
- Self-adaptive IR supplement
- 5-metre IR distance
- Alarm In/Out
- PoE + DC12V
- IP66 + IK9

PORTABLE SSD / MOBILE NAS

T100I



Variants:
DS-USSD - 120G - T100I
DS-USSD - 240G - T100I
DS-USSD - 480G - T100I

- Up to 480 GB capacity
- Up to 450 MB/s reading speed, 6 times better than HDD
- Hanging Hole Design
- Shock-Proof and Fall-Proof

W100I



Variants:
DS-UAFS-W100/120G
DS-UAFS-W100/240G

- Built-in SSD, High Speed R/W
- Vibration resistant and supports up to 240 GB storage.
- USB Type-C 3.1 interface.
- Resource Sharing
- Supports concurrent access by up to 10 users.
- Durable Portable Power
- 6700 mAh large capacity battery to charge mobile phone and tablet.
- Watch up to 11 hours of online video through HiStor app.
- Connection Through QR Codes
- Small and Light, 208.8 g (0.46 lb), handy and portable.

MONITORS

LCD-P22FHD-VH



- 22" LCD
- LED backlit technology with full HD 1920×1080
- Wide view angle: 170° (H)/160° (V)
- Multiple inputs: HDMI, VGA
- HDMI/VGA output at 1080p resolution
- 3D comb filter, 3D De-interlace
- 3D noise reduction
- VESA stand bracket

LCD-P22FHD-VHBA



- 22" LCD
- LED backlit technology with full HD 1920×1080
- Wide view angle: 170° (H)/160° (V)
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction
- Multiple inputs: HDMI, VGA, BNC, audio in
- Multiple outputs: BNC, audio output
- Built-in speaker
- External video play via USB port
- VQD (Video Quality Diagnostics)
- Highly reliable components for 24/7 operation
- VESA stand bracket

LCD-P19HD-VH



- 19" LCD
- LED backlit technology with HD 1366×768
- Wide view angle: 90° (H)/65° (V)
- 3D comb filter
- 3D De-interlace
- 3D noise reduction
- Input: HDMI, VGA
- VESA stand bracket



HOME



SMB



HiWatch



FACTORY



PROPERTY



FLEXIBILITY BY DESIGN
HiWATCH – SUITABLE FOR MULTIPLE APPLICATIONS

2017 Q3 |

QUARTERLY FEATURED PRODUCTS

HIKVISION[®]
HiWatch Series