

## DS-2CE71D8T-PIRLO 2 MP Ultra Low Light PIR Fixed Turret Camera



- 2 MP high performance PIR turret camera
- PIR detection, strobe light alarm and alarm out to warn off intruders in real time
- Strong night performance, capturing images in ultra-low light down to 0.003 lux
- Clear imaging even against strong back lighting due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- EXIR 2.0: advanced infrared technology with 20 m IR distance
- Water and dust resistant (IP67)






## ▪ Specification

Camera	
Image Sensor	2MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.003 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°
Signal System	PAL/NTSC
Light Alarm	Yes
Lens	
Lens Type	2.8 mm, 3.6 mm fixed focal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 103.5°, vertical FOV: 55°, diagonal FOV: 119° 3.6 mm, horizontal FOV: 79.1°, vertical FOV: 43°, diagonal FOV: 92°
Lens Mount	M12
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, DNR, Mirror, Smart IR
Frame Rate	TVI: 1080p@25fps/30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	≥130 dB
White Balance	Auto/Manual
White Light	AUTO/OFF
AGC	Support
Interface	
Video Output	1 HD analog output
General	
Material	Front cover: Metal Main body: Plastic
Dimension	Φ 109.8 mm × 89.75 mm (Φ 4.32" × 3.53")
Weight	Approx. 327 g (0.72 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera.
Consumption	Max. 3.9 W
IR Range	Up to 20 m
Approval	
Protection	IP67

## ▪ Available Model

DS-2CE71D8T-PIRLO

**▪ Accessory****▪ Optional**

<b>DS-1272ZJ-110-TRS</b> Wall Mount	<b>DS-1275ZJ-SUS</b> Vertical Pole Mount	<b>DS-1276ZJ-SUS</b> Corner Mount	<b>DS-1280ZJ-S</b> Junction Box	<b>DS-1281ZJ-S</b> Inclined Ceiling Mount
				

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

