

## DS-D4239TI-SLC Transparent LED Display



The full-color transparent LED display standard series, featuring with high brightness, high contrast, and ultra-wide viewing angle, can achieve quality display effects from different viewing angles. Designed with light and thin structure, the transparent LED display is small in size and cost-effective in maintenance, which is widely applicable to glass curtain wall, glass shopcase, commercial complex, space design, etc.

- Standardized cabinet for flexible installation, multi-screen seamless splicing with light and thin design, and convenient for quick installation.
- Permeability-oriented material selection and design, no influence on the original building appearance.
- Brightness customizable on the basis of specific scenarios, ensuring the display effects even under the highlight indoor or the direct sunlight outdoor.
- Runs silently with lower heat and effective heat dissipation.



## ▪ Specification

Model		DS-D4239TI-SLC
<b>Cabinet</b>	Pixel Configuration	1R1G1B
	Pixel Pitch	Horizontal: 3.9 mm, Vertical: 7.8 mm
	Dimensions (W × H × D)	Different dimensions for flexible splicing: 1 m × 1 m, 1 m × 0.75 m, 0.75 m × 1 m, 0.75 m × 0.75 m, 1 m × 1.25 m, 1.25 m × 1 m
	Weight	15 kg/m <sup>2</sup>
	Pixel Density	32768 dot/m <sup>2</sup>
	Cabinet Material	Aluminum alloy
	Protection Level	IP43
<b>Display</b>	White Balance Brightness	5500 nit (highlight)
	Color Temperature	2000K to 10000K adjustable
	Viewing Angle	120° (H)/120° (V)
	Brightness Uniformity	≥ 98%
	Color Uniformity	± 0.001 Cx, Cy
	Contrast Ratio	≥ 3000:1
	Transmittance	60%
	Display Color	281.4 trillion
<b>Processing Performance</b>	Brightness Control	Manual/Auto
	Driving Method	Constant current driving 1/4 scan
	Frame Frequency	60 Hz
	Refresh Rate	≥ 1920 Hz
	Grey Level	65536 Level
	Processing Depth	16 bits
<b>Power</b>	Max. Consumption	800 W/m <sup>2</sup>
	Average Consumption	300 W/m <sup>2</sup>
	Input Voltage	110 to 220 VAC ± 15%
<b>Working Environment</b>	Working Temperature	-10 °C to 65 °C (14 °F to 149 °F)
	Working Humidity	10% to 90%
	Storage Temperature	-20 °C to 90 °C (-4 °F to 194 °F)
	Storage Humidity	10% to 90%

**▪ Available Model**

DS-D4239TI-SLC

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com