



Dock station provides you with an easy way to access body cameras, and collect, store, and play audio, video, and picture files in the connected body cameras.

- Dual system design which is highly stable. Supports wall mount, mobile mount, and desktop mount.
- 13.3-inch ultra-large touchscreen with 1920 × 1080 resolution and convenient operation.
- Unlocks body camera bin by recognizing face to guarantee safe device storage.
- Equipped with eight body camera bins in standard. Four dock stations can be connected. Up to 32 body cameras can be connected simultaneously. Supports auto charging.
- Two standard USB interfaces provided. One is used to connect to a mouse or keyboard for software operation, or connect to a USB flash disk to upgrade the dock station. The other one is reserved.
- Supports six hard disks. Standard 2 TB storage capacity. Up to 8 TB for each disk. RAID0, RAID1, and RAID5 can be customized.
- Supports auto uploading of body camera data (picture, video, and audio), and clearing the storage space of body camera automatically.
- Locks important data of body camera to avoid being deleted.
- Supports data protection in sudden power cutoff.
- Log management to record all the operation logs.
- Overwritten storage to overwrite the collected data according to the collection sequence when the storage is full.
- ANR for data uploading to prevent data loss.
- Supports file search in multiple modes, and video, audio, and picture playback.
- Local upgrade.
- Multi-user management. Multi-users can be associated with one dock station.
- Files can be uploaded to CVR and cloud storage.

*Notes:

*Wall-mounted bracket and bracket assembly are required for the dock station DS-MDS003/DS-MDS005.

*Wall mount: Please order the bracket (DS-MH1901 or DS-MH1902).

*Desktop and mobile mount: Please order the bracket (DS-MH1901 or DS-MH1902) and the bracket assembly (DS-MH1601 or DS-MH1602).



•

Specification

| Screen | |
|-----------------------------|---|
| Screen Size | 13.3 inch |
| Resolution | 1920 × 1080 |
| Touchscreen | Capacitive touchscreen |
| Smart Function | |
| Face Picture Comparison | Body camera access by face picture comparison |
| General | |
| Operating System | Linux, Android 5.1.1 |
| Memory | 2 GB |
| Indicator | Charging indicator, working indicator |
| Button | Power Button |
| Product Weight | 18.295 kg (40.334 lb.) |
| Product Dimension | 635 mm × 604.6 mm × 108.7 mm (25" × 23.8" × 4.3") |
| Package Weight | 24.1 kg (53.13 lb.) |
| Package Dimension | 793 mm × 393 mm × 578 mm (31.2" × 15.5" × 22.8") |
| Ingress Protection | IP20 |
| Power Supply Mode | External power supply |
| Working Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Working Humidity | RH (93 ± 3)% |
| Storage Temperature | -25 °C to 50 °C (-13 °F to 122 °F) |
| Light Supplement | |
| White Light | Supported |
| Storage | |
| Number of Extended Storage | 6 |
| Extended Storage Media | Hard Disk |
| Extended Storage Capacity | Max. 8 T for one |
| Peripheral Device Interface | |
| Charging Interface | Three-phase plug |
| External Interface | RJ45, RS-232, USB 2.0, USB 3.0 |
| Loudspeaker | Supported |

Available Model

DS-MDS003/2T/8 DS-MDS001/6T/8 DS-MDS001-8S DS-MDS003/2T/8 DS-MDS003-E DS-MDS003/2T/8/TYPEC



Dimension

289.8

325

œ

Ņ

13

0 0

F

325









F

 $\left[\right]$

P



Unit: mm





Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ





(O) hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 I Data subject to change without notice I