

Type 3 Scr Internal Alarm Cable LSF to BS4737 - 3.30:2015



Cable Construction 8 Core

| | |
|--------------------|------------------------------|
| Conductor | Tinned Copper Clad Aluminium |
| Conductor Diameter | TCCA 0.20 ±0.008 |
| Stranded Diameter | 0.61 |

Insulation PVC

| | |
|--------------------------|--|
| Thickness (mm) | 0.2x7 |
| Insulation Diameter (mm) | 1.0 ±0.10mm |
| Insulation Colours | White, Yellow, Green, Black, Blue, Red, Orange |
| Thickness (mm) | 0.3x1 |
| Insulation Diameter (mm) | 1.2 ±0.10mm |
| Insulation Colours | Brown (Centre) |

Drain Wire

| | |
|-------------------|---------------------|
| Construction (mm) | TCCA 0.20 ± 0.008x7 |
| AL-PET Shield | >=115% |
| Nylon Rip-Cord | Yellow 210D |

Jacket LSF

| | |
|-------------------|----------------|
| Nominal Thickness | 0.50mm |
| Diameter (mm) | 4.60±0.20 |
| Jacket Colour | White RAL 9003 |
| Marking | 001m.....100m |

Electrical Characteristics

| | |
|-------------------------------|------------------|
| Max Conductor DC Resistance | 20°C Ω/100m 155 |
| Minimum Insulation Resistance | 20°C [MΩ/M] >200 |
| Rated Temperature | 80°C |
| Rated Voltage | 30V |

Our Other Products Include

Coaxial Cable

RG & URM Coaxial

CCTV Coaxial

Composite / Hybrid

TV / Satellite

Digital Coaxial

Networking Cable

Cat5E UTP/FTP (100 MHz)

Cat6 UTP/FTP (250 MHz)

Cat6A U/FTP (500 MHz)

Cat7 S/FTP (600 MHz)

Data Cabinets

Wall & Floor Standing Cabinets

Server Cabinets

Cabinet Accessories

Alarm Cable

TCCA

Premium BS4737

Belden Style Cable

Single Pair Cable

Overall Shielded Cores

Overall Shielded Pairs

Foil & Braid Shielded Pairs

Individually Shielded Pairs

Bus / Profi-Bus

Telecom Cable

Budget Telecom

CW1308

CW1128/98

Bell Wire

Speaker Cable

Budget 13/42/79 Strands

Oxygen Free

Fire Resistant Cable

Standard / Enhanced

Mineral Insulated

Accessories

Defence Standard

7/0.2

16/0.2