

Belden Style OSC4-18 9418 LSZH

Our Other Products Include



Cable Construction 4 Cores

Conductor	Tinned Copper : T0.25±0.008 x 19
Stranded Dia.	1.26
Al-Pet Shield	>=115%
Drain wire	Tinned Copper : T0.20±0.008x7
Construction	T0.32±0.008 x 7

Jacket LSZH

Dia.(mm)	6.20(±0.20)
Jacket Color	Grey RAL7042
Thickness(mm)	0.8

Insulation SR-PVC

Thickness (mm)	0.27
Insulation Dia. (mm)	1.8±0.15×4C

Colours

Red , Black, White, Green

Marking

OSC4 4x18AWG 600V Overall Screened LSZH RoHS2 Order No +0001m...

Electrical Characteristics

Max.Conductor DC Resistance at 20°C (Ω/Km)	<19.97
Rated Temperature(°C)	70
Rated Voltage(V)	600
20°C Insulation Resistance(MΩ.M)	>200

Coaxial Cable

- RG & URM Coaxial
- CCTV Coaxial
- Composite / Hybrid
- Digital Coaxial

Networking Cable

- Cat5E UTP/FTP (100 MHz)
- Cat6 UTP/FTP (250 MHz)
- Cat6A U/FTP (500 MHz)
- Cat7 S/FTP (600 MHz)

Data Cabinets

- Server Cabinets
- Cabinet Accessories

Alarm Cable

TCCA

Premium BS4737

Belden Style Cable

- Single Pair Cable
- Overall Shielded Cores
- Overall Shielded Pairs
- Foil & Braid Shielded Pairs
- Individually Shielded Pairs

Bus / Profi-Bus

Telecom Cable

- Budget Telecom
- CW1308
- CW1128/98
- Bell Wire

Speaker Cable

- Budget 13/42/79 Strands
- Oxygen Free

Fire Resistant Cable

- Standard / Enhanced
- Mineral Insulated
- Accessories

Defence Standard

- 7/0.2
- 16/0.2